



## Low Cost, L1 GPS+GLONASS Receiver Enhances Satellite Availability and Positioning

### Benefits

Increased satellite availability with GLONASS tracking

Easy to integrate

Form-factor consistent with Superstar II and OEMV-1/1G/1DF receivers<sup>1</sup>

NovAtel OEMV®-style command interface

### Features

Small form factor

Very low power consumption

GL1DE® firmware option

### Designed for Integration

The OEMStar receiver has the same form factor as NovAtel's Superstar II and OEMV-1/1G/1DF receivers. This allows customers to easily integrate the OEMStar into existing Superstar II and OEMV-1/1G/1DF systems<sup>1</sup>. The OEMStar uses Space Based Augmentation System (SBAS) corrections from services such as the Wide Area Augmentation System (WAAS) and the European Geostationary Navigation Overlay Service (EGNOS).

### Multi-Constellation Performance

The OEMStar offers GPS+GLONASS positioning and measurements in combination with GPS data to provide increased satellite availability for positioning in challenging environments at a very cost-effective price.

### Code and Carrier Phase

The OEMStar features up to 14 channels of combined L1 GPS and GLONASS code and carrier phase tracking for increased positioning accuracy and availability. The position, velocity and time information is available at up to 10 Hz, with a 1 PPS accuracy of 20 ns.

### Small Form Factor with Low Power Consumption

The OEMStar measures only 46 by 71 mm, accepts an input voltage between 3.3 and 5.0 VDC and consumes less than 500 mW. This makes the OEMStar an attractive choice for use in handheld and battery powered applications.

If you require more information about our receivers, visit [novatel.com/products/gnss-receivers/oem-receiver-boards](http://novatel.com/products/gnss-receivers/oem-receiver-boards)



[novatel.com](http://novatel.com)

[sales@novatel.com](mailto:sales@novatel.com)

1-800-NOVATEL (U.S. and Canada)  
or 403-295-4900

Europe 44-1993-85-24-36

SE Asia and Australia 61-400-833-601

## Performance<sup>2</sup>

### Channel Configuration

14 GPS L1  
 12 GPS L1 + 2 SBAS  
 10 GPS L1 + 4 GLO L1  
 8 GPS L1 + 6 GLO L1  
 8 GPS L1 + 4 GLO L1 + 2 SBAS  
 10 GPS L1 + 2 GLO L1 + 2 SBAS

### Horizontal Position Accuracy (RMS)

Single Point L1 1.5 m  
 SBAS<sup>3</sup> 0.7 m  
 DGPS 0.5 m

### Measurement Precision (RMS)

	GPS	GLO
L1 C/A Code	5 cm	35 cm
L1 Carrier Phase	0.6 mm	1.5 mm

### Data Rate

Measurements up to 10 Hz  
 Position up to 10 Hz

### Time to First Fix

Cold Start<sup>4</sup> 65 s  
 Hot Start<sup>5</sup> 35 s

### Signal Reacquisition

L1 < 1.0 s (typical)

**Time Accuracy<sup>3,6</sup>** 20 ns RMS

**Velocity Accuracy** < 0.05 m/s RMS

**Velocity<sup>7</sup>** 515 m/s

## Physical and Electrical

**Dimensions** 46 x 71 x 13 mm

**Weight** 18 g

### Power

Input Voltage +3.3 VDC +5%/-5%  
 Power Consumption<sup>8</sup> 0.360 W

### Antenna LNA Power Output

Output Voltage 5 V nominal  
 Maximum Current 100 mA

### Communication Ports

- 2 LV-TTL serial ports capable of 300 to 230,400 bps
- 1 USB 2.0 full speed client port

### Input/Output Connectors

Main 20-pin dual row male header  
 Antenna Input MCX female

### Environmental

Temperature  
 Operating -40°C to +85°C  
 Storage -45°C to +90°C  
 Humidity 95% non-condensing

Random Vibe MIL-STD 810G

Sine Vibe IEC 60068-2-6 (5 g)

Shock MIL-STD 810G

## Options and Accessories

- GPS-700 series antennas
- ANT series antennas
- RF Cables—5, 10 and 30 m lengths
- Right angle RF connector

## Additional Firmware Features

- GL1DE

## Additional Features

- Auxiliary strobe signals, including a configurable PPS output for time synchronization and mark inputs
- Outputs to drive external LEDs
- Common, field-upgradeable software



Version 2 - Specifications subject to change without notice.

©2010 NovAtel Inc. All rights reserved.

NovAtel, GL1DE and OEMV are registered trademarks of NovAtel Inc.

OEMStar is a trademark of NovAtel Inc.

Printed in Canada. D13800

OEMStar November 2010

For the most recent details of this product:

[novatel.com/Documents/Papers/OEMStar.pdf](http://novatel.com/Documents/Papers/OEMStar.pdf)

<sup>1</sup> Physical size, mounting holes and connector location is identical to Superstar II and OEMV-1/1G receivers. Some of the 20-pin connector signal assignments have been modified.

<sup>2</sup> Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

<sup>3</sup> GPS only.

<sup>4</sup> Typical value. No almanac or ephemerides and no approximate position or time.

<sup>5</sup> Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

<sup>6</sup> Time accuracy does not include biases due to RF or antenna delay.

<sup>7</sup> Export licensing restricts operation to a maximum of 515 metres per second.

<sup>8</sup> Typical values for 14 channel GPS only operation. Power consumption will vary depending upon features selected.

